

Monitor LCD NVM-423LCD



Features

- Professional high resolution TFT LCD monitor
 - Digital 3D comb filter for sharp and clear picture with natural colors
 - Panel type: 23"
 - 16:9 LCD panel format
 - 4-channel real-time multiplexer built-in
 - Multi-screen display (PC/Quad/POP screen/Full screen)
 - Image storage: up to 60 still images
 - Digital zoom: 2x
 - Alarm input/output: 1
 - Video input: 4 x BNC, S-Video, VGA, RCA
 - Audio input: RCA
 - Internal speakers
 - Key Lock function and menu password protection
 - Multi-lingual On Screen Display (OSD)
 - Rugged metal design
 - Power supply: 24 VDC (100 ~ 240 VAC/24 VDC PSU in-set included)

| Specifications | Description |
|-------------------------|--|
| Panel Type | 23" color TFT LCD Panel |
| Screen Size (Diagonal) | 584.2 (mm) |
| Viewable Size (mm) | 501.12 x 300.67 (mm) |
| CRT Dot Pitch | 0.391 x 0.391 (mm) |
| Resolution | 580 TVL |
| Viewing Angle (L/R/T/B) | 85°/85°/85°/85° |
| Contrast Ratio | 400:1 |
| Brightness | 450 cd/m ² |
| Display Color | 16.7 mln |
| Response Time | 25 ms |
| Video Input | 4 x CVBS: BNC loop-through connector, 1 x S-Video: Mini-DIN 4 Pin connector, 1 x VGA, 1 x YPbPr: 3 x RCA |
| Audio Input | Stereo 1 Vp-p/1 kHz |
| Speaker Output | 2 x 2.5 W |
| Alarm Input | 1 input (NO/NC) with individual polarity selection |
| Alarm Output | 1 output (NO/NC) |
| Operation | Multi-lingual On Screen Display (OSD) |
| Operation System | PAL/NTSC (Auto Scan) |
| Case | Metal |
| Access Security | Key Lock function, menu password protection |

| Specifications | Description |
|-----------------------|--|
| Power Supply | 24 VDC (100 ~ 240 VAC/24 VDC PSU in-set included) |
| Power Consumption | 101 W |
| Operating Temperature | 0°C ~ 40°C |
| Dimensions (mm) | 572 (W) x 385 (H) x 68.9 (D) |
| Weight | 9.5 kg |
| In-set Included | DC adapter, Power cord, VGA cable, IR remote control |