

Day/Night IR Bullet Camera NVC-GDN3803H/IRH-2



Features

- Mechanical IR cut filter
- IR operation capability
- Horizontal resolution: up to 700 TVL
- Min. Illumination: from 0.00003 lx/F=1.2 (DSS) (0 lx - IR On)
- Wide Dynamic Range (WDR) for enhanced image quality in diverse light conditions
- Digital Slow Shutter (DSS)
- High Light Compensation (HLC)
- Digital Image Stabilizer (DIS)
- Digital Noise Reduction (DNR)
- IR-smart function
- Lens type: auto-iris DC lens, f=6~50 mm
- Digital zoom: 16x
- Privacy zones: 12
- 1 alarm output triggered by motion detection
- Other functions: various picture effects, motion detection (8 zones)
- Full configuration (user friendly multi-lingual OSD):
 - directly from the camera
 - from the NV-KBD70 & NV-KBD40 keyboards
 - from NOVUS® video capture cards
 - directly from the front panel of selected NOVUS® DVR models
- Remote control: RS-485
- Protocols: Pelco-D, Pelco-P
- Built-in IR LED - 100 pcs.
- IP 66
- Built-in fan & heater
- Power supply: 12 VDC/24 VAC

Specifications	Description
Pick-up Element	1/3" SONY Super HAD II CCD imager
Number of effective pixels	752 (H) x 582 (V)
Horizontal Resolution	600 TVL – color mode, 700 TVL – B/W mode
Min. Illumination	0.05 lx/F=1.2 - color mode (1/50 s), 0.005 lx/F=1.2 - B/W mode (1/50 s), 0.0001 lx/F=1.2 - color mode, DSS, 0.00003 lx/F=1.2 - B/W mode, DSS, 0 lx (IR On)
S/N Ratio	52 dB (AGC Off)
Electronic Shutter	Auto (AES): 1/50 s ~ 1/120 000 s
Digital Slow Shutter (DSS)	1/25 s ~ 10.24 s
Auto Gain Control (AGC)	On/Off (2 levels)
Wide Dynamic Range (WDR)	On/Off
White Balance	5 modes: Manual/AWC/Outdoor/Indoor/ATW

Specifications	Description
Back Light Compensation (BLC)	On/Off (3 modes)
High Light Compensation (HLC)	On/Off (3 modes)
Synchronization	Internal
Day/Night Switching	Auto/Manual
Filter Delay	3 s/5 s/7 s/10 s/15 s/20 s/30 s/40 s/60 s
Lens Type	auto iris DC lens f=6 ~ 50 mm
Angle of View (H)	43.6° ~ 5.5°
Zoom	16x
IR LED	100 pcs.
IR Effective Range	Up to 100 m
Flickerless function	On/Off
Video Output	1.0 Vp-p/75 Ohm (BNC)
Alarm Output	1 relay output
Remote Control	RS-485
Protocol	Pelco-D, Pelco-P
Set-up	Multi-lingual On Screen Display (OSD)
Privacy Zones	12
Other Functions	Digital Image Stabilizer (DIS), Digital Noise Reduction (DNR), Motion detection, Various picture effects: Mirror (horizontal) and 180° image rotation, Image sharpness adjustment
Enclosure	Aluminium body with sunshield and fully-cable-managed mounting bracket for indoor/outdoor, wall/in-ceiling mount
Degree of Protection	IP 66
Power Supply	12 VDC/24 VAC
Power Consumption	18 W (IR & heater On)
Operating Temperature	-40°C ~ 50°C
Dimensions (mm)	140 (W) x 220 (H) x 470 (L)
Weight	3 kg