

Day/Night Classic Camera

NVC-HDN5602C-2



*lens not included



Features

- Mechanical IR cut filter
- IR operation capability
- Horizontal resolution: up to 680 TVL
- Min. illumination: from 0.00002 lx/F=1.2 (DSS)
- Wide Dynamic Range (WDR) for enhanced image quality in diverse light conditions
- Digital Slow Shutter (DSS)
- Digital Noise Reduction (DNR)
- High Light Compensation (HLC)
- Privacy zones: 8
- Other functions: mirror picture effect, negative, image sharpness adjustment, image contrast adjustment, motion detection
- Dead Pixel Correction (DPC)
- Full configuration directly from the camera (user friendly multi-lingual OSD)
- Power supply: 12 VDC/24 VAC

Specifications	Description
Pick-up Element	1/3" SONY SUPER HAD II CCD imager
Number of effective pixels	752 (H) x 582 (V)
Horizontal Resolution	630 TVL - color mode 680 TVL - B/W mode
Min. Illumination	0.07 lx/F=1.2 - color mode (1/50 s), 0.007 lx - B/W mode (1/50 s), 0.00002 lx/F=1.2 - B/W mode (DSS)
S/N Ratio	>52 dB (AGC off)
Electronic Shutter	auto (AES): 1/50 s ~ 1/100 000 s
Digital Slow Shutter (DSS)	0.04 s ~ 20.84 s
Auto Gain Control (AGC)	On/Off (3 levels)
Wide Dynamic Range (WDR)	On/Off
White Balance	3 modes: Manual/AWC/ATW
Back Light Compensation (BLC)	On/Off
High Light Compensation (HLC)	On/Off
Synchronization	Internal
Day/Night Switching	Auto/Manual
Filter Delay	1~15 s
Iris Mode	D
Lens Mount	C/CS
Flickerless function	On/Off

Specifications	Description
Video Output	BNC, 1.0 Vp-p, 75 Ohm
Set-up	On Screen Display (OSD)
Privacy Zones	8
Other Functions	Digital Noise Reduction (DNR), Motion detection, Various picture effects: Mirror, Negative, Image sharpness adjustment, Image contrast adjustment
Power Supply	12 VDC/24 VAC
Power Consumption	2 W
Operating Temperature	-10°C ~ 50°C
Dimensions (mm)	108 (L) x 65 (W) x 52 (H)
Weight	230 g