

noVus

Classic AHD Camera

NVAHD-1DN5100C-1

5000
AHD SERIES



FUNCTIONS



KEY FEATURES

- D/N function - IR cut filter
- resolution 720p
- optional UTC remote controller
- Min. Illumination from 0.0003 lx

DIMENSIONS



Image	
Image Sensor	CMOS sensor 1/3" SONY
Operating mode	AHD 720p, analog 960H
Number of Effective Pixels	1280 (H) x 1024 (V)
Resolution	720p
Min. Illumination	0.18 lx/F1.2 - color mode, 0.003 lx/F1.2 - B/W mode, 0.0003 lx/F1.2 - color mode (DSS), 0.0003 lx/F1.2 - B/W mode (DSS)
S/N Ratio	> 52 dB (AGC off)
Electronic Shutter	auto/manual: 1/25 s ~ 1/50000 s (AHD), 1/50 s ~ 1/50000 s (analog 960H)
Digital Slow Shutter (DSS)	up to 30x
High Light Compensation (HLC)	yes
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Lens	
Compatible Mount Type	C, CS
Iris Mode	D
Day/Night	
Switching Type	mechanical IR cut filter
Switching Mode	auto, manual
Switching Level Adjustment	yes
Switching Delay	0 ~ 60 s
Other functions	
OSD	languages: Polish, English, Russian, others
Privacy Zones	4
Motion Detection	yes
Image Processing	180° image rotation, sharpening, mirror effect
Remote control	Yes (optional UTC remote control)*
Interfaces	
Video Output	BNC, 1.0 Vp-p, 75 Ohm
Installation parameters	
Dimensions (mm)	58 (W) x 62 (H) x 125 (L)
Weight	0.34 kg
Enclosure	aluminium, white
Power Supply	12 VDC
Power Consumption	1.6 W
Operating Temperature	-30°C ~ 40°C

* Remote controller type: NV-RCUTC-35HD / Lens not included