




# IP Recorder

## NVR-6332P16-H4



### FUNCTIONS




### COMPATIBILITY



### KEY FEATURES

- 16 x PoE Ethernet ports
- 32 x video and audio channels
- Recording speed up to 960 fps at 3840 x 2160
- Supports resolution up to 3840 x 2160
- Recorded stream size: 256 Mb/s in total from all cameras
- 4 x internal place for HDD mounting
- 2 x monitor outputs (HDMI 4K UltraHD, VGA)
- Intelligent image analysis

### DIMENSIONS



| Video                               |  |
|-------------------------------------|--|
| Maximum Supported Camera Resolution | 3840 x 2160  |
| Compression                         | H.264, H.264+, H.265   |
| Monitor Output                      | main (split screen, full screen, sequence): 1 x HDMI (4K UltraHD), 1 x VGA (up to 2 monitors simultaneously)   |
| Dualstreaming Support               | yes*   |
| Audio                               |  |
| Audio Input/Output                  | - / 1 x line-out (RCA)   |
| Recording                           |  |
| Recording Speed                     | 960 fps (32 x 30 fps for 1280 x 720),<br>960 fps (32 x 30 fps for 1920 x 1080),<br>960 fps (32 x 30 fps for 2048 x 1536),<br>960 fps (32 x 30 fps for 2560 x 1440)   |
| Stream Size                         | 256 Mb/s in total from all cameras   |
| Recording Mode                      | continuous, triggered by: manual, alarm input, motion detection  |
| Prealarm/Postalarm                  | up to 5 s/up to 600 s  |
| Display                             |  |
| Display Speed                       | 960 fps (32 x 30 fps)**  |
| Playback                            |  |
| Playback Speed                      | 480 fps (16 x 30 fps for 1280 x 720) **,<br>480 fps (16 x 30 fps for 1920 x 1080) **,<br>480 fps (16 x 30 fps for 2048 x 1536) **,<br>480 fps (16 x 30 fps for 2560 x 1440) **,<br>480 fps (16 x 30 fps for 2592 x 1944) **,<br>480 fps (16 x 30 fps for 3840 x 2160) ** |
| Recorded Data Search                | by date/time, events   |
| Backup                              |  |
| Backup Methods                      | USB port (HDD or Flash memory), network  |
| Backup File Format                  | AVI  |
| Storage                             |  |
| Internal Storage                    | available mount: 4 x HDD 3.5" 8 TB SATA  |
| Total Internal Capacity             | 32 TB  |
| Alarm                               |  |
| Internal Alarm Input/Output         | 16/4 relay type  |
| Camera Alarm Input/Output           | supports IP camera's alarm input/output *  |
| Motion Detection                    | supports camera's motion detection*  |
| System Reaction to Alarm Events     | buzzer, e-mail, alarm output activation, recording activation, PTZ   |
| Intelligent image analysis          |  |
| Supported Functions                 | Exception, Scene Change, Video Blurred, Video Color Cast, Tripwire, Zone entrance, Abandoned Object, Object Disappearance  |
| Network                             |  |
| Network Interface                   | 1 x Ethernet - RJ-45 interface, 10/100 Mbit/s<br>16 x Ethernet PoE (IEEE802.3af, Class 3) - RJ-45 interface, 10/100 Mbit/s   |
| Network Protocols Support           | HTTP, TCP/IP, IPV4, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTSP, UPnP, SNMP, SMTP   |
| PC/MAC Software                     | NMS, Internet Explorer, NVR-6000 Viewer/Safari   |
| Mobile applications                 | SuperLive Plus (iPhone, Android)   |
| Number of Simultaneous Connections  | up to 4 clients  |
| Bandwidth                           | 256 Mb/s in total to all client workstations   |
| PTZ                                 |  |
| PTZ Functions                       | pan/tilt/zoom, preset commands*  |
| Auxiliary Interfaces                |  |
| USB Ports                           | 1 x USB 2.0, 1 x USB 3.0,  |
| Operating system                    |  |
| Operating System                    | Linux  |
| Operation Mode                      | triplex  |
| OSD                                 | languages: Polish, English, others   |
| Control                             | PC mouse and IR remote controller (in-set included), network   |
| System Diagnostic                   | automatic control of: HDDs, network, camera connection loss  |
| Security                            | password protection, IP filtering, MAC filtering   |
| Installation parameters             |  |
| Dimensions (mm)                     | 440 (W) x 70 (H) x 390 (D)   |
| Weight                              | 4.4 kg (without HDD)   |
| Power Supply                        | 100 ~ 240 VAC  |
| Power Consumption                   | 60 W (with 4 HDDs) + 246 W PoE   |
| Operating Temperature               | -10°C ~ 50°C   |

Support for intelligent image analysis works only with NOVUS IP 3000 series cameras

\* Function depends on communication protocol, for details please check compatibility table in section DOWNLOADABLE FILES.

\*\* Available with dual streaming mode.