



NMS Client Station

NVSO CLIENT 7-4U-II - PRODUKT ARCHIWALNY



FUNCTIONS



KEY FEATURES

- Monitoring of up to 120 channels
- Supports resolution up to 4000 x 3000
- Supports up to 6 monitors simultaneously
- Operating system: Microsoft Windows 10 Pro
- Compatible with all NMS Network Video Recorders
- Integration with: recorders AHD NOVUS, systems of SSWiN DSC, systems of NMS ANPR, systems POS (Posnet, Upos i inne)

DIMENSIONS



| Video | |
|-------------------------------------|--|
| Supported Cameras/Protocols | NOVUS |
| Maximum Supported Camera Resolution | 4000 x 3000 |
| Monitor Output | main (split screen, full screen, sequence): 2 x HDMI, 2 x Display Port, 2 x DVI-D (up to 6 monitors simultaneously)* |
| Dualstreaming Support | yes |
| Audio | |
| Audio Input/Output | - / 1 x line-out (Jack 3.5 mm), 1 x S/PDIF (optical) |
| Display | |
| Display Speed | 2250 fps (75 x 30 fps for 1280 x 720)**, 1800 fps (60 x 30 fps for 1920 x 1080)**, 900 fps (60 x 15 fps for 2048 x 1536)**, 720 fps (60 x 12 fps for 2592 x 1944)** |
| Playback | |
| Recorded Data Search | by date/time, events, "Text-in" |
| Backup | |
| Backup Methods | USB port (HDD or Flash memory), network |
| Storage | |
| Internal storage for system | built-in: 1 x HDD 3,5" SATA |
| Network | |
| Network Interface | 1 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s |
| Bandwidth | 250 Mb/s in total from all NVRs |
| Network Protocols Support | HTTP, TCP/IP, IPv4, UDP, FTP, DHCP, DNS, NTP, RTSP, UPnP, SMTP |
| Mobile applications | NMS Mobile |
| PTZ | |
| PTZ Functions | pan/tilt/zoom, preset commands, patterns, tours, auto-scans*** |
| Auxiliary Interfaces | |
| USB Ports | 2 x USB 2.0, 6 x USB 3.0, |
| Operating system | |
| Operating System | Microsoft Windows 10 Pro |
| Operation Mode | triplex |
| OSD | languages: Polish, English, Russian, others |
| Control | PC mouse and keyboard (in-set included), network, DCZ keyboard |
| System Diagnostic | automatic control of: HDDs, network, camera connection loss |
| Security | password protection, IP filtering, limiting the number of connections |
| Installation parameters | |
| Dimensions (mm) | 483 (W) x 177 (H) x 505 (D) |
| Weight | 25 kg |
| Power Supply/Power Consumption | built-in PSU 230 VAC/700 W |
| Operating Temperature | 5°C ~ 35°C |
| RACK Mount 19" | 4U |

* To support more than four monitors it is required to use Display Port output.

** Available with dual streaming mode.

*** Function capability depends on used devices and communication protocols.