



IP user monitor

NVE-M200LITE



The **NVE-M200** IP user monitor is an elegant and aesthetically made device designed for installation in a residential or office space. The large color screen and intuitive menu allows quick and convenient use of its functions. In addition to the basic functions (camera image display, door opening), the on-screen menu also allows you to view and delete messages and photos. The device's basic memory allows you to save up to 100 photos or 10 videos. Built-in speaker and microphone facilitate operation and communication with guests, security of the building or other premises. Communication with another subscriber is also possible by receiving and sending text messages entered from the keyboard displayed on the screen. The door opening command from the icon on the screen can be additionally password protected. Optionally eight input lines can create a simple alarm system enriched with images from cameras. The subscriber is armed / disarmed by means of an icon on the screen. The alarm is signaled locally and on the security monitor. Disabling the alarm requires a special password.

Device type	IP Indoor monitor
Display	LCD TFT
Resolution	1024 x 600 px
Diagonal	7"
Power supply input	12 V DC
PoE	48 V DC (802.3af)
Power consumption	300mA
Additional functions	alarm functions, SD card slot, volume control, monitoring of the view from cameras, intercom calls, text messages, voice mail, photos and video recording
Dimensions	210 x 140 x 20 mm
Operating temperature	from -10 to 55 °C