



# Wall/ceiling mount bracket with built-in PoE switch

NVS-4020JBD



## KEY FEATURES

- 2 x 100Mb/s PoE
- 1 x 100Mb/s UPLINK

## DIMENSIONS



Wall/ceiling mount bracket, indoor/outdoor, for mounting two cameras.

A detailed list of compatible cameras and other products and accessories, can be found in the file available in the "Downloadable File" section.

| GENERAL                 |   |
|-------------------------|---|
| Managed                 | no  |
| Device Type             | PoE Switch  |
| NETWORK                 |   |
| Ports                   | PoE Ports: 2 x 10Mb/s / 100Mb/s<br>UPLINK ports: 1 x 10Mb/s / 100Mb/s |
| PoE standards           | IEEE802.3af, Class 3  |
| Surge protection        | Maximum voltage: 4kV  |
| Switching capacity      | 1 Gb/s  |
| FUNCTIONS               |   |
| Surge protection        | yes   |
| INSTALLATION PARAMETERS |   |
| Case                    | Glass fiber reinforced polyamide, color white                         |
| Dimensions (mm)         | 310 (W) x 70 (H) x 156 (L)  |
| Weight                  | 1.2 g   |
| Degree of Protection    | IP 66 (details in the user's manual)                                  |
| Input Voltage           | PoE+  |
| Power Consumption       | 30 W (maximum)  |
| PoE Budget              | 25 W for ports 1 to 2, up to 15 W for one port                        |
| Operating Temperature   | -30°C ~ 60°C  |
| Humidity                | max. 90%, relative (non-condensing)                                   |