



IP Entrance panel

NVE-EPV102P



NVE-EPV102P villa entrance panel is an elegant and aesthetic device designed for outdoor use, e.g. in front of the entrance to the property. It allows to easily communicate with the homeowners using the bell button and the built-in color camera. IR illumination allows trouble-free use of the panel also at night. The built-in Unique 125 kHz proximity card reader allows to create a simple access control and facilitates the daily use of the system. Support for two relays allows to control both the wicket and the gate.

Included:

- IP Entrance panel
- wall bracket
- 2x fixing screws and expansion bolts
- inner hexagon screw
- allen wrench
- 3x proximity tag
- RJ45 adapter
- nameplate sticker
- thimble
- short manual

| | |
|---------------------------|---|
| Device type | IP Entrance panel |
| Number of users | 2 |
| Sensor | CMOS HD 2 MPx |
| Resolution | 1920 x 1080 px |
| View angle | 120 ° |
| Video coding | H.265 (default); H.264 |
| Power supply input | 15 V DC |
| PoE | 48 V DC (802.3af) |
| Power consumption | 300mA 4,5 W (Max.) |
| Lock output | NO Relay (4 A / 36 V DC/AC) |
| Gate output | NO Relay (4 A / 36 V DC/AC) |
| Port LAN | 1 x 10M / 100M Ethernet |
| Wi-Fi | No |
| Standalone mode | No |
| Card reader format | Unique |
| Number of cards supported | 100 |
| Numeric keyboard | No |
| Access Code | No |
| Additional functions | LED IR, mounting on an angular bracket, Status LEDs |
| Dimensions | 154 x 55 x 21 mm |
| Weight | 380g |
| Protection code | IP66 |
| IK Rating | IK07 |
| Operating temperature | from -40 to 60 °C |
| Color | Graphite black (RAL9011) |