



# NOVUS MANAGEMENT SYSTEM VSS IP Recorder

NMS VSS NVR 7-4U-III



## FUNCTIONS



## COMPATIBILITY



## KEY FEATURES

- Video and audio channels: 150
- Recording speed up to 3750 fps at 1920 x 1080
- Supports resolution up to 4000 x 3000
- Recorded stream size: 350 Mb/s in total from all cameras
- Supports up to 3 monitors simultaneously
- optional disk mounting: 6 x SATA 3,5"
- Operating system: Microsoft Windows 10 IoT
- Recording and surveillance system: NOVUS MANAGEMENT SYSTEM VSS
- Compatible with all NOVUS IP cameras

## DIMENSIONS



RACK Mount 19"	4U
<b>Video</b>	
IP Camera Recording	120 channels at 1920x1080 (video+audio) using H.264 codec 150 channels at 1920x1080 (video+audio) using H.265 codec
Maximum Supported Camera Resolution	4000x3000
Supported Codes	H.264, H.264+, H.265, H.265+, MJPEG
Supported Cameras and Protocols	Novus, Novus fisheye, ONVIF, ONVIF fisheye, RTSP, RTSP fisheye (purchase of the appropriate license is required)
Dualstreaming Support	yes
<b>Display</b>	
Monitor Output	1 x HDMI 2.0b, 1 x Display Port 1.4, 1 x Dual link DVI-D (up to 3 monitors simultaneously)
Maximum Resolution	3 x 4K UltraHD
<b>Audio</b>	
Audio input	1 x Line in (3,5mm), 1 x Mic in(3,5mm)
Audio Output	1 x Line (3,5mm), 1 x HDMI, 1 x Display Port
Audio Input/Output in Cameras	Supports audio input/output build in cameras
<b>Performance - H.264</b>	
2MPX IP Camera	Recording up to: 120 main streams (while displaying: 8 sub streams) Display up to: 70 sub streams or 20 main streams (while recording: 70 main streams) Playback up to: 20 main streams (while recording: 70 main streams)
4MPX IP Camera	Recording up to: 70 main streams (while displaying: 8 sub streams) Display up to: 70 sub streams or 13 main streams (while recording: 70 main streams) Playback up to: 13 main streams (while recording: 70 main streams)
5MPX IP Camera	Recording up to: 60 main streams (while displaying: 8 sub streams) Display up to: 60 sub streams or 8 main streams (while recording: 60 main streams) Playback up to: 8 main streams (while recording: 60 main streams)
8MPX IP Camera	Recording up to: 40 main streams (while displaying: 8 sub streams) Display up to: 40 sub streams or 5 main streams (while recording: 40 main streams) Playback up to: 5 main streams (while recording: 40 main streams)
12MPX IP Camera	Recording up to: 35 main streams (while displaying: 8 sub streams) Display up to: 35 sub streams or 4 main streams (while recording: 35 main streams) Playback up to: 4 main streams (while recording: 35 main streams)
<b>Performance - H.265</b>	
2MPX IP Camera	Recording up to: 150 main streams (while displaying: 8 sub streams) Display up to: 55 sub streams or 15 main streams (while recording: 55 main streams) Playback up to: 15 main streams (while recording: 55 main streams)
4MPX IP Camera	Recording up to: 100 main streams (while displaying: 8 sub streams) Display up to: 50 sub streams or 8 main streams (while recording: 50 main streams) Playback up to: 8 main streams (while recording: 50 main streams)
5MPX IP Camera	Recording up to: 80 main streams (while displaying: 8 sub streams) Display up to: 60 sub streams or 5 main streams (while recording: 60 main streams) Playback up to: 5 main streams (while recording: 60 main streams)
8MPX IP Camera	Recording up to: 70 main streams (while displaying: 8 sub streams) Display up to: 65 sub streams or 4 main streams (while recording: 65 main streams) Playback up to: 4 main streams (while recording: 65 main streams)
12MPX IP Camera	Recording up to: 56 main streams (while displaying: 8 sub streams) Display up to: 32 sub streams or 4 main streams (while recording: 32 main streams) Playback up to: 4 main streams (while recording: 32 main streams)
<b>Recording</b>	
Recording Mode	Continuous, Schedule, Panic, Triggered: manually, by alarm input, motion detection, video analysis, POS, temperature alarm
Schedule	individual settings for: each camera, each day of the week, specific days (holidays etc.), configuration with an accuracy of: 15 min, possibility of combining individual recording modes
Prealarm/Postalarm	Up to: 30s / Up to: 600s
<b>Playback</b>	
Recorded Data Search	By Date/Time, Events, "Text-in"
<b>Backup</b>	
Backup Methods	USB port (HDD Ior Flash drive), Network
Backup File Format	JPEG, BMP, AVI, NMS
<b>HDD</b>	
Internal storage for system	1 x SSD NVMe
Internal Storage for Recording	6 available bays for 3,5" HDD surveillance grade storage media
<b>Alarms</b>	
Alarm Input/output in cameras	support of alarm input and output built in cameras
Motion detection	support of motion detection built in cameras
Video Analytics	supported built in analytics in camera
Temperature alarm	support of temperature alarm built in cameras
Licence plate recognition (LPR)	support of selected image analysis functions available in the camera
System Reactions to Alarm Events	e-mail, Screen Message, Recording Activation, PTZ
<b>Network</b>	
Network Interface	1 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s 1 x Ethernet - złącze RJ45, 10/100/1000/2500 Mbit/s
Network Throughput	up to 350Mbit/s from all cameras, up to 350Mbit/s to all client stations, Max network throughput: 350Mbit/s for each network card
Network Protocols Support	HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, FTP, DHCP, DNS, DDNS, RTSP, RTP, SAMBA
Compatible Mobile Applications	NMS Mobile
<b>PTZ</b>	
PTZ Functions	pan, tilt, zoom, preset commands, patterns, tours, auto-scans, focus, iris
<b>Additional interfaces</b>	
USB Ports	4 x USB 3.2,

Operating System	
Operating System	Microsoft Windows 10 IoT
Recording and Surveillance System	NOVUS MANAGEMENT SYSTEM VSS
Operation Mode	Pentaplex
OSD	Polish, English, Russian, others
Control	PC mouse and keyboard (in-set included), DCZ keyboard
System Diagnostic	automatic control of: HDDs, Temperature, Fan, Network, Camera connection loss
Security	Password protection, IP filtering, MAC filtering, Limiting the number of connections
Integration	
Integrated Devices	Novus IP Cameras, Novus IP Recorders, Novus AHD Recorders, POS Systems (Posnet, Upos and other), ONVIF Devices, RTSP Devices
Installation Parameters	
Dimensions (mm)	482 (W) x 178 (H) x 505 (D)
Weight	24 kg (without HDDs for recording)
Power Supply	built in 700W, with 230VAC input
Power consumption/heatprint	280W/230W (without HDD for recording)
Operating Temperature	5°C ~ 35°C
RACK Mount 19"	4U

*Note: The device requires registration and license activation. There is an option to activate a 60-day trial license. After this period, the purchase of a NOVUS MANAGEMENT SYSTEM VSS software license specific to the application is required. To choose the appropriate license, please contact the sales department.*