

# noVus

## Dome Camera

### NVC-402D/IR-white

**400**  
SERIES



#### FUNCTIONS

**960H**



#### KEY FEATURES

- D/N function - electronic
- Resolution: 650 TVL
- Lens: fixed focal, f=3.6 mm/F2.0
- IR LED, range up to 15 m
- Smart IR function
- Extended IR LED life
- Min. Illumination: 0.14 lx (0 lx, IR on)

#### DIMENSIONS



| Image                         |                                                       |
|-------------------------------|-------------------------------------------------------|
| Image Sensor                  | CCD sensor 1/3" SONY Super HAD II                     |
| Number of Effective Pixels    | 976 (H) x 582 (V)                                     |
| Horizontal Resolution         | 650 TVL - color mode, 650 TVL - B/W mode              |
| Min. Illumination             | 0.14 lx/F2.0 - color mode,<br>0 lx (IR on) - B/W mode |
| S/N Ratio                     | > 52 dB (AGC off)                                     |
| Electronic Shutter            | auto: 1/50 s ~ 1/100000 s                             |
| High Light Compensation (HLC) | +                                                     |
| Wide Dynamic Range (WDR)      | yes                                                   |
| Digital Noise Reduction (DNR) | 2D                                                    |
| Defog Function (F-DNR)        | no                                                    |
| Lens                          |                                                       |
| Lens Type                     | fixed focal, f=3.6 mm/F2.0                            |
| Day/Night                     |                                                       |
| Switching Type                | electronic D/N function                               |
| Switching Mode                | auto, manual *                                        |
| Switching Level Adjustment    | yes *                                                 |
| Switching Delay               | 0 ~ 255 s *                                           |
| Other functions               |                                                       |
| OSD                           | graphical languages: English, Russian, others *       |
| Privacy Zones                 | 4 *                                                   |
| Motion Detection              | yes                                                   |
| Motion Detection              | *                                                     |
| Image Processing              | sharpening, mirror effect *                           |
| IR LED                        |                                                       |
| LED Number                    | 24                                                    |
| Range                         | 15 m                                                  |
| Angle                         | 80°                                                   |
| Interfaces                    |                                                       |
| Video Output                  | BNC, 1.0 Vp-p, 75 Ohm                                 |
| Installation parameters       |                                                       |
| Dimensions (mm)               | 112 (Ø) x 87 (H)                                      |
| Weight                        | 0.20 kg                                               |
| Enclosure                     | plastic, white                                        |
| Power Supply                  | 12 VDC                                                |
| Power Consumption             | 1.1 W,<br>3.2 W (IR illuminator on)                   |
| Operating Temperature         | -30°C ~ 40°C                                          |