



Vandal Proof IP Camera with Motor-zoom Lens

NVIP-8DN3512V/IR-1P



FUNCTIONS



KEY FEATURES

- Resolution: 8 MPX (4K Ultra HD)
- Lens: motorized, auto-focus function, $f=3.3 \sim 12$ mm/F1.4
- D/N function - IR cut filter
- Video content analysis
- microSD card support
- Min. Illumination: 0.01 lx (0 lx, IR on)
- IR LED, range up to 30 m

DIMENSIONS



Image	
Image Sensor	8 MPX CMOS sensor 1/2.5" SONY Exmor R STARVIS
Number of Effective Pixels	3840 (H) x 2160 (V)
Min. Illumination	0.01 lx/F1.4 - color mode, 0 lx (IR on) - B/W mode
Electronic Shutter	auto: 1/25 s ~ 1/100000 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Defog Function (F-DNR)	yes
Highlight Compensation (HLC)	yes
Back Light Compensation (BLC)	yes
Lens	
Lens Type	motorized, $f=3.3 \sim 12$ mm/F1.4
Auto-focus	zoom trigger, day/night mode trigger, manual trigger
Day/Night	
Switching Type	mechanical IR cut filter
Switching Mode	auto, manual, time, light sensor
Switching Level Adjustment	yes
Switching Schedule	yes
Visible Light Sensor	yes
Network	
Stream Resolution	3840 x 2160 (4K Ultra HD), 1920 x 1080 (Full HD), 1280 x 720 (HD), 720 x 576 (D1), 352 x 288 (CIF)
Frame Rate	30 fps for and lower resolutions
Multistreaming Mode	number of streams: 3
Video/Audio Compression	H.264, H.265, MJPEG/G.711
Number of Simultaneous Connections	max. 4
Bandwidth	50 Mb/s in total
Network Protocols Support	HTTP, TCP/IP, IPv4, UDP, FTP, DHCP, DDNS, NTP, RTP, PPPoE, SMTP
ONVIF Protocol Support	Profile S (ONVIF 2.3)
Camera Configuration	from Internet Explorer, Firefox, Chrome, Opera browser languages: Polish, English, Russian, and others
Compatible Software	NOVUS MANAGEMENT SYSTEM VSS
Video Analytics	
Functions	tamper, abandoned object, object disappearance, line cross, zone entrance, scene change, video blurred, video color cast
Other functions	
Privacy Zones	4
Motion Detection	yes
Region of interest (ROI)	8
Image Processing	90° image rotation, 180° image rotation, sharpening, mirror effect
Prealarm/Postalarm	-/up to 120 s
System Reaction to Alarm Events	e-mail with attachment, saving file on FTP server, saving file on SD card, alarm output activation
IR LED	
LED Number	30
Range	30 m
Angle	90°
Interfaces	
Video Output	BNC, 1.0 Vp-p, 75 Ohm - maintenance only
Audio Input/Output	1 x Jack (3.5 mm)/1 x Jack (3.5 mm)
Alarm Input/Output	1 (NO/NC)/1
Network Interface	1 x Ethernet - RJ-45 interface, 10/100 Mbit/s
Memory Card Slot	microSD - capacity up to 128GB
Installation parameters	
Dimensions (mm)	150 (Ø) x 114 (H)
Weight	1.00 kg
Degree of Protection	IP 66 (details in the user's manual)
Enclosure	vandalproof, IK10 impact rating, aluminium, white, poly-carbonate bubble
Power Supply	12 VDC, PoE (IEEE 802.3af, Class 3)
Power Consumption	4.5 W, 6.5 W (IR illuminator on)
Operating Temperature	-20°C ~ 50°C

Settings for stream 60 FPS @ 1080p are available from firmware 3.4.3(2016-8-17) up.