

noVus

Dome Camera
NVC-401D-black

400
SERIES



FUNCTIONS



KEY FEATURES

- D/N function - electronic
- Resolution: 650 TVL
- Lens: fixed focal, f=3.6 mm/F2.0
- Min. Illumination: 0.14 lx

DIMENSIONS



70 mm

100 mm (Ø)



Image	
Image Sensor	CCD sensor 1/3" SONY Super HAD II
Number of Effective Pixels	976 (H) x 582 (V)
Horizontal Resolution	650 TVL - color mode, 650 TVL - B/W mode
Min. Illumination	0.14 lx/F2.0 - color mode
S/N Ratio	> 52 dB (AGC off)
Electronic Shutter	auto: 1/50 s ~ 1/100000 s
High Light Compensation (HLC)	yes
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D
Lens	
Lens Type	fixed focal, f=3.6 mm/F2.0
Day/Night	
Mode	electronic D/N function
Switching Mode	auto, manual
Switching Level Adjustment	yes
Switching Delay	0 ~ 255 s
Other functions	
OSD	graphical languages: English, Russian, others
Privacy Zones	4
Motion Detection	yes
Image Processing	sharpening, mirror effect
Interfaces	
Video Output	BNC, 1.0 Vp-p, 75 Ohm
Installation parameters	
Dimensions (mm)	100 (Ø) x 70 (H)
Weight	0.2 kg
Enclosure	plastic, black
Power Supply	12 VDC
Power Consumption	0.9 W
Operating Temperature	-30°C ~ 45°C