

# NOVUS

## IP Recorder


NVR-6332-H8/F



6000

VSS  
IP

### FUNCTIONS



### KEY FEATURES

- 32 x video and audio channels
- Recording speed up to 960 fps at 3840 x 2160
- Supports resolution up to 3840 x 2160
- Recorded stream size: 256 Mb/s in total from all cameras
- 8 x internal place for HDD mounting
- 3 x monitor outputs (HDMI 4K UltraHD, HDMI, VGA)
- Face recognition

### DIMENSIONS



| Video                               |   |
|-------------------------------------|---|
| Maximum Supported Camera Resolution | 3840 x 2160   |
| Compression                         | H.264, H.264+, H.265  |
| Monitor Output                      | main (split screen, full screen, sequence): 1 x HDMI (4K UltraHD), 1 x VGA<br>spot: 1 x HDMI (FullHD)                                       |
| Dualstreaming Support               | yes*  |
| Audio                               |   |
| Audio Input/Output                  | - / 1 x line-out (RCA)  |
| Recording                           |   |
| Stream Size                         | 256 Mb/s in total from all cameras  |
| Recording Mode                      | continuous, triggered by: manual, alarm input, motion detection   |
| Prealarm/Postalarm                  | up to 5 s/up to 600 s   |
| Display                             |   |
| Display Speed                       | 960 fps (32 x 30 fps)*  |
| Playback                            |   |
| Playback Speed                      | 480 fps (16 x 30 fps for 3840 x 2160) *   |
| Recorded Data Search                | by date/time, events, related to face recognition   |
| Backup                              |   |
| Backup Methods                      | USB port (HDD or Flash memory), network   |
| Backup File Format                  | AVI   |
| Storage                             |   |
| Internal Storage                    | available mount: 8 x HDD 3.5" 14 TB SATA  |
| Total Internal Capacity             | 112 TB  |
| Alarm                               |   |
| Internal Alarm Input/Output         | 8/4 relay type (max. 12VDC/1A)  |
| Camera Alarm Input/Output           | supports IP camera's alarm input/output   |
| Motion Detection                    | supports camera's motion detection  |
| System Reaction to Alarm Events     | buzzer, e-mail, alarm output activation, recording activation, PTZ  |
| Intelligent image analysis          |   |
| Supported Functions                 | Exception, Scene Change, Video Blurred, Video Color Cast, Tripwire, Zone entrance, Abandoned Object, Object Disappearance, Face Recognition |
| Database Capacity                   | 5000 faces<br>1000 license plates   |
| Network                             |   |
| Network Interface                   | 2 x Ethernet - RJ-45 interface, 10/100/1000 Mbit/s  |
| Network Protocols Support           | HTTP, TCP/IP, IPv4, HTTPS, FTP, DHCP, DNS, DDNS, NTP, RTP, RTSP, UPnP, SNMP, SMTP   |
| PC/MAC Software                     | Internet Explorer, NVR-6000 Viewer/NVR-6000 Viewer  |
| Mobile applications                 | SuperLive Plus (iPhone, Android)  |
| Number of Simultaneous Connections  | up to 4 clients   |
| Bandwidth                           | 256 Mb/s in total to all client workstations  |
| PTZ                                 |   |
| PTZ Functions                       | pan/tilt/zoom, preset commands  |
| Auxiliary Interfaces                |   |
| USB Ports                           | 2 x USB 2.0, 1 x USB 3.0  |
| Operating system                    |   |
| Operating System                    | Linux   |
| Operation Mode                      | triplex   |
| OSD                                 | languages: Polish, English, others  |
| Control                             | PC mouse and IR remote controller (in-set included), network  |
| System Diagnostic                   | automatic control of: HDDs, network, camera connection loss   |
| Security                            | password protection, IP filtering, MAC filtering  |
| Installation parameters             |   |
| Dimensions (mm)                     | 445 (W) x 90 (H) x 436 (D)  |
| Weight                              | 6 kg (without HDD)  |
| Power Supply                        | 100 ~ 240 VAC   |
| Power Consumption                   | 175 W (with 8 HDDs)   |
| Operating Temperature               | -10°C ~ 50°C  |

Support for intelligent image analysis works only with NOVUS IP 3000 series cameras

The availability of the following functions: double-stream operation, motion detection, alarm inputs / outputs, PTZ control depends on the functionality of the given camera and the capabilities of the communication protocol. Detailed data can be found in the compatibility table available in the DOWNLOADS tab.

\* Available with dual streaming mode.