## NoVus

## **NVSO IP Recorder**

NVSO 5-T-II



## FUNCTIONS



3750 fps













- •Video and audio channels: 150
- •Recording speed up to 3750 fps at 1920 x 1080
- •Supports resolution up to 4000 x 3000
- •Recorded stream size: 350 Mb/s in total from all cameras

- From all cameras

  Supports up to 3 monitors simultaneously

  optional disk mounting: 5 x SATA 3,5"

  Operating system: Microsoft Windows 10 Pro

  Compatible with all NOVUS IP cameras

## DIMENSIONS







|  |  | 1 | 0.00 |
|--|--|---|------|
|  |  |   |      |
|  |  |   |      |
|  |  |   |      |

| Video                               |  |
|-------------------------------------|--|
| IP Camera Recording                 | 120 channels at 1920x1080 (video+audio) using H.264 codec<br>150 channels at 1920x1080 (video+audio) using H.265 codec   |
| Maximum Supported Camera Resolution | 4000x3000  |
| Supported Codes                     | H.264, H.264+, H.265, H.265+, MJPEG  |
| Supported Cameras and Protocols     | Novus, Novus fisheye, ONVIF, ONVIF fisheye, RTSP, RTSP fisheye   |
| Dualstreaming Support               | yes  |
| Display                             |  |
| Monitor Output                      | 1 x HDMI 2.0b, 1 x Display Port 1.2, 1 x Dual link-DVI (up to 3 monitors simultaneously)   |
| Maximum Resolution                  | 3 x 4K UltraHD   |
| Audio                               |  |
| Audio input                         | 1 x Line in (3,5mm), 1 x Mic in(3,5mm)   |
| Audio Output                        | 1 x Line (3,5mm), 1 x HDMI, 1 x Display Port   |
| Audio Input/Output in Cameras       | Supports audio input/output build in cameras   |
| Performance - H.264                 |  |
| 2MPX IP Camera                      | Recording up to: 120 main streams (while displaying: 8 sub streams) Display up to: 50 sub streams or 12 main streams (while recording: 50 main streams) Playback up to: 12 main streams (while recording: 50 main streams) |
| 4MPX IP Camera                      | Recording up to: 70 main streams (while displaying: 8 sub streams) Display up to: 45 sub streams or 8 main streams (while recording: 45 main streams) Playback up to: 8 main streams (while recording: 45 main streams)    |
| SMPX IP Camera                      | Recording up to: 60 main streams (while displaying: 8 sub streams) Display up to: 45 sub streams or 6 main streams (while recording: 45 main streams) Playback up to: 6 main streams (while recording: 45 main streams)    |
| 8MPX IP Camera                      | Recording up to: 40 main streams (while displaying: 8 sub streams) Display up to: 40 sub streams or 4 main streams (while recording: 40 main streams) Playback up to: 4 main streams (while recording: 40 main streams)    |
| 12MPX IP Camera                     | Recording up to: 35 main streams (while displaying: 8 sub streams) Display up to: 35 sub streams or 4 main streams (while recording: 35 main streams) Playback up to: 4 main streams (while recording: 35 main streams)    |
| Performance - H.265                 |  |
| 2MPX IP Camera                      | Recording up to: 150 main streams (while displaying: 8 sub streams) Display up to: 30 sub streams or 8 main streams (while recording: 30 main streams) Playback up to: 8 main streams (while recording: 30 main streams)   |
|                                     | Recording up to: 100 main streams (while displaying: 8 sub streams)  |

| 410 mm | 8MPX IP Camera      | Display up to: 40 sub streams or 4 main streams (while recording: 40 main streams) Playback up to: 4 main streams (while recording: 40 main streams)  |
|--------|---------------------|---|
|        | 12MPX IP Camera     | Recording up to: 35 main streams (while displaying: 8 sub streams) Display up to: 35 sub streams or 4 main streams (while recording: 35 main streams) Playback up to: 4 main streams (while recording: 35 main streams)       |
|        | Performance - H.265 |   |
|        | 2MPX IP Camera      | Recording up to: 150 main streams (while displaying: 8 sub streams) Display up to: 30 sub streams or 8 main streams (while recording: 30 main streams) Playback up to: 8 main streams (while recording: 30 main streams)      |
|        | 4MPX IP Camera      | Recording up to: 100 main streams (while displaying: 8 sub streams) Display up to: 30 sub streams or 4 main streams (while recording: 30 main streams) Playback up to: 4 main streams (while recording: 30 main streams)      |
|        | 5MPX IP Camera      | Recording up to: 80 main streams (while displaying: 8 sub streams)<br>Display up to: 35 sub streams or 4 main streams (while recording: 35 main streams)<br>Playback up to: 4 main streams (while recording: 35 main streams) |
|        | 8MPX IP Camera      | Recording up to: 75 main streams (while displaying: 8 sub streams)<br>Display up to: 35 sub streams or 2 main streams (while recording: 35 main streams)<br>Playback up to: 2 main streams (while recording: 35 main streams) |
|        | 12MPX IP Camera     | Recording up to: 56 main streams (while displaying: 8 sub streams)<br>Display up to: 20 sub streams or 2 main streams (while recording: 20 main streams)<br>Playback up to: 2 main streams (while recording: 20 main streams) |

| 12MPX IP Camera                  | Recording up to: 56 main streams (while displaying: 8 sub streams) Display up to: 20 sub streams or 2 main streams (while recording: 20 main streams) Playback up to: 2 main streams (while recording: 20 main streams) |
|----------------------------------|---|
| Recording                        |   |
| Recording Mode                   | Continuous, Schedule, Panic, Triggered: manually, by alaram input, motion detection, video analysis, POS, temerature alarm  |
| Schedule                         | individual settings for: each camera, each day of the week, specific days (holidays etc.), configuration with an accuracy of: 15 min, possibility of combining individual recording modes                               |
| Prealarm/Postalarm               | Up to: 30s / Up to: 600s  |
| Playback                         |   |
| Recorded Data Search             | By Date/Time, Events, "Text-in"   |
| Backup                           |   |
| Backup Methods                   | USB port (HDD lor Flash drive), Network   |
| Backup File Format               | JPEG, BMP, AVI, NMS   |
| HDD                              |   |
| Internal storage for system      | 1 x HDD 3.5" SATA   |
| Internal Storage for Recording   | 5 available bays for 3,5" HDD surveillance grade storage media  |
| Alarms                           |   |
| Alarm Input/output in cameras    | support of alarm input and output built in cameras  |
| Motion detection                 | support of motion detection built in cameras  |
| Video Analytics                  | supported built in analytics in camera  |
| Temperature alarm                | support of temperature alarm built in cameras   |
| Licence plate recognition (LPR)  | support of selected image analysis functions available in the camera  |
| System Reactions to Alarm Events | e-mail, Screen Message, Recording Activation, PTZ   |
| Network                          |   |
| Network Interface                | 1 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s   |
| Network Throughput               | up to 350Mbit/s from all cameras,<br>up to 350Mbit/s to all client stations,  |

| Licence plate recognition (LPR)  | support of selected image analysis functions available in the came  |  |
|----------------------------------|---|--|
| System Reactions to Alarm Events | e-mail, Screen Message, Recording Activation, PTZ   |  |
| Network                          |   |  |
| Network Interface                | 1 x Ethernet - RJ45 interface, 10/100/1000 Mbit/s   |  |
| Network Throughput               | up to 350Mbit/s from all cameras,<br>up to 350Mbit/s to all client stations,<br>Max network throughput: 350Mbit/s for each network card |  |
|                                  |   |  |

HTTP, TCP/IP, IPv4/v6, UDP, HTTPS, Multicast, FTP, DHCP, DNS, DDNS, NTP, RTSP, SAMBA Network Protocols Support

PTZ Functions Additional interfaces Operating System Microsoft Windows 10 Pro

Recording and Surveillance System NMS (Novus Management System) Additional Software Internet Explorer

| OSD                         | Polish, English, Russian, others  |
|-----------------------------|---|
| Control                     | PC mouse and keyboard (in-set included), DCZ keyboard   |
| System Diagnostic           | automatic control of: HDDs, Temperature, Fan, Network, Camera connection loss   |
| Security                    | Password protection, IP filtering, MAC filtering, Limiting the number of connections  |
| Integration                 |   |
| Integrated Devices          | Novus IP Cameras, Novus IP Recorders, Novus AHD Recorders, NMS-ANPR Software, DSC Systems, POS<br>Systems (Posnet, Upos and other), ONVIF Devices, RTSP Devices |
| Installation Parameters     |   |
| Dimensions (mm)             | 160 (W) x 428 (H) x 410 (D)   |
| Weight                      | 10 kg (without HDDs for recording)  |
| Power Supply                | built in 700W, with 230VAC input  |
| Power consumption/heatprint | 260W/210W (without HDD for recording)   |
| Operating Temperature       | 5°C ~ 35°C  |

Attention:
To support more than 1 RTSP stream and 1 ONVIF stream you will need special licence key.
From serial number: XX 2417 4170, devices have Microsoft Windows 10 Pro operating system.
Performance specifications described in the above are valid from serial WA 2519 5776