# Bullet AHD Multistandard Camera

NHDC-2H-6101L



## FUNCTIONS




## KEY FEATURES

•D/N function - IR cut filter
•resolution 1080p
•Lens: fixed focal, f=2.8 mm/F2.2
•Smart IR function
•multistandard: AHD, CVI, TVI, 960H
•IR LED, range up to 20 m

## DIMENSIONS




| | |
|---|---|
| **Image** | |
| Image Sensor | CMOS sensor 1/2.7" SUPERPIX |
| Operating mode | AHD 1080p, AHD 720p, TVI 1080p, TVI 720p, CVI 1080p, CVI 720p, analog 960H |
| Number of Effective Pixels | 1920 (H) x 1080 (V) |
| Resolution | 1080p |
| Min. Illumination | 0 lx (IR on) - B/W mode |
| S/N Ratio | > 52 dB (AGC off) |
| Electronic Shutter | auto/manual: 1/50 s ~ 1/100000 s |
| Wide Dynamic Range (WDR) | yes |
| Digital Noise Reduction (DNR) | 2D |
| **Lens** | |
| Lens Type | fixed focal, f=2.8 mm/F2.2 |
| **Day/Night** | |
| Mode | day/night switching: mechanical IR cut filter |
| Switching Mode | auto, manual |
| Visible Light Sensor | yes |
| **Other functions** | |
| OSD | languages: English, others |
| Image Processing | Defective Pixel Correction (DPC), sharpening |
| Remote control | Yes (COAX protocol) |
| **IR LED** | |
| LED Number | 1 |
| Range | 20 m |
| Smart IR | yes (software support) |
| **Interfaces** | |
| Video Output | BNC, 1.0 Vp-p, 75 Ohm |
| **Installation parameters** | |
| Dimensions (mm) | with bracket: 75 (W) x 75 (H) x 170 (L) |
| Weight | 0.25 kg |
| Degree of Protection | IP 66 (details in the user's manual) |
| Power Supply | 12 VDC |
| Power Consumption | 1 W,<br>4 W (IR illuminator on) |
| Operating Temperature | -30°C ~ 50°C |
| Humidity | max. 90%, relative (non-condensing) |