



Bullet AHD Multistandard Camera

NHDC-2H-6302



FUNCTIONS

MULTI
STANDARD



1080p
Resolution



KEY FEATURES

- D/N function - IR cut filter
- resolution 1080p
- Lens: varifocal, f=2.8 ~ 12 mm/F1.4
- Smart IR function
- multistandard: AHD, CVI, TVI, 960H
- IR LED, range up to 50 m

DIMENSIONS



Image	
Image Sensor	CMOS sensor 1/2.9" SMARTSENS
Operating mode	AHD 1080p, AHD 720p, TVI 1080p, CVI 1080p, CVI 720p, analog 960H
Number of Effective Pixels	1920 (H) x 1080 (V)
Resolution	1080p
Min. Illumination	0 lx (IR on) - B/W mode
S/N Ratio	> 52 dB (AGC off)
Electronic Shutter	auto/manual: 1/50 s ~ 1/100000 s
Wide Dynamic Range (WDR)	yes
Digital Noise Reduction (DNR)	2D, 3D
Lens	
Lens Type	varifocal, f=2.8 ~ 12 mm/F1.4
Day/Night	
Switching Type	mechanical IR cut filter
Switching Mode	auto, manual
Visible Light Sensor	yes
Other functions	
OSD	languages: English, others
Image Processing	Defective Pixel Correction (DPC), sharpening
Remote control	Yes (COAX protocol)
IR LED	
LED Number	2
Range	50 m
Smart IR	yes (software support)
Interfaces	
Video Output	BNC, 1.0 Vp-p, 75 Ohm
Installation parameters	
Dimensions (mm)	with bracket: 81 (W) x 81 (H) x 220 (L)
Weight	0.61 kg
Degree of Protection	IP 67 (details in the user's manual)
Enclosure	aluminium, white, fully cable managed wall mount bracket in-set included
Power Supply	12 VDC
Power Consumption	1 W, 4 W (IR illuminator on)
Operating Temperature	-30°C ~ 50°C
Humidity	max. 90%, relative (non-condensing)