



IP/WIFI Entrance panel

NVE-EPV101KPWIFI



KEY FEATURES:

- Number of users: 1
- Camera with 1920 x 1080 px resolution and 120° viewing angle, IR illumination
- Proximity card reader in the unique 125 kHz standard
- Dual Band 2.4/5 GHz Wi-Fi, RTSP protocol support
- Autonomous mode (without monitor) with gate and door control function
- Mounting on an angle bracket with a rain cover
- Connection to a mobile app via Wi-Fi

The Villa NVE-EPV101KPWIFI entrance panel is an elegant and aesthetic device designed for outdoor use, e.g. in front of the entrance to a property. It allows you to easily communicate with the homeowner using the call button and built-in color camera. IR backlighting allows for trouble-free use of the panel even at night. The built-in proximity card reader in the unique 125 kHz standard and the numeric keypad allow you to create simple access control and facilitate everyday use of the system. Support for two relays allows you to control both the gate and the door. A third relay allows you to connect an additional doorbell. Thanks to the use of WiFi technology, the panel can also work autonomously with the Tuya Smart app and/or wirelessly with user monitors. The panel supports the RTSP protocol, making it possible to stream to Novus CCTV recorders. Image parameters, settings, and network protocols can be configured from the web app client.

Included:

- IP Entrance panel
- WIFI antenna
- wall bracket
- 2x fixing screws and expansion bolts
- inner hexagon screw
- allen wrench
- 3x proximity tag
- RJ45 adapter
- nameplate sticker
- thimble
- short manual

| | |
|----------------------------|--|
| Device type | IP Entrance panel |
| Number of users | 1 |
| Sensor | CMOS HD 2 MPx |
| Resolution | 1920 x 1080 px |
| View angle | 120 ° |
| Video coding | H.265 (default); H.264 |
| Power supply input | 15 V DC |
| Power consumption | 300mA 4,5 W (Max.) |
| Lock output | NO Relay (4 A / 36 V DC/AC) |
| Gate output | NO Relay (4 A / 36 V DC/AC) |
| Ringbell output | NO Relay (4 A / 36 V DC/AC) |
| Exit Button | No |
| Door open status indicator | No |
| Port LAN | 1 x 10M / 100M Ethernet |
| Wi-Fi | Dual Band 2,4 GHz/5 GHz (IEEE 802.11 a/b/g/n) |
| Standalone mode | Yes |
| Card reader format | unique standard |
| Number of cards supported | 100 |
| Numeric keyboard | Yes |
| Access Code | Yes |
| Additional functions | LED IR, mobile application via WIFI, mounting on an angular bracket, Status LEDs, Stand alone mode |
| Dimensions | 154 x 55 x 21 mm |
| Weight | 380g |
| Protection code | IP66 |
| IK Rating | IK07 |
| Operating temperature | from -40 to 60 °C |
| Color | Graphite black (RAL9011) |