# 43'' 4K LCD monitor designed for continuous operation

NVM-6043LCD-4K

## FUNCTIONS

## KEY FEATURES

- dedicated to continuous operation (24/7)
- anti-glare panel coating eliminating reflections
- short response time (8ms) preventing blurring of dynamic image parts
- image correction options to help you capture all the details even in difficult lighting conditions
- LED backlight with dynamic brightness adjustment

## DIMENSIONS

| | |
|---|---|
| **LCD PANEL** | |
| Panel Type | IPS, LED backlight |
| Surface treatment | Anti-glare treatment (haze 25%), 3H hard coating |
| Screen Size (Diagonal) | 43" |
| Panel Resolution | 3840 x 2160 |
| Viewable area | 941.2 x 529.1 mm |
| Pixel pitch | 0.245 mm |
| Format | 16:9 |
| Brightness | 350 cd/m2 |
| Contrast Ratio | 1000:1 |
| Viewing Angle (H/V) | 178°/178° |
| Response Time | 8 ms |
| Refresh frequency | 60 Hz (max) |
| Display Color | 16.7 mln (gamut: sRGB: 92%, DCI-P3: 74%) |
| **Other functions** | |
| OSD | languages: Polish, English |
| Split image functions | picture-in-picture (PIP) display, display video from inputs in split-screen format (PBP)<br>PBP screen split: 2, 3 or 4 windows |
| Digital Filter | 3D |
| Built-in Speakers | 2 x 3 W |
| **Interfaces** | |
| Video Input | 3 x HDMI, 1 x Display Port |
| Audio Input | 3 x HDMI (stereo), 1 x DisplayPort (stereo) |
| External Control | Infrared remote control |
| Other Connectivity | USB 2.0 (for service) |
| **Installation parameters** | |
| Dimensions (mm) | 969 (W) x 615 (H) x 202 (D) |
| Weight | 12 kg |
| Case | black, plastic |
| Power Supply | 100 ~ 240 VAC |
| Power Consumption | 40 W (max)<br>0.5 W (in standby mode)<br>0.1 W (in off mode) |
| Operating Temperature | -10°C ~ +60°C |
| Humidity | 15% - 85%, relative (non-condensing) |
| Mounting Standard | VESA 200 x 200 mm |