# 4-Port Ethernet PoE+ Switch

NVS-3404SP



## FUNCTIONS

NDAA

## KEY FEATURES

- 4 x 10/100Mbps PoE+
- 2 x 100Mb/s UPLINK
- Operation mode: VLAN, Extend, PoE Watchdog

## DIMENSIONS



44 mm

200 mm



118 mm



| | |
|---|---|
| **GENERAL** | |
| Device Type | PoE+ Switch |
| **NETWORK** | |
| Ports | PoE+ Ports: 4 x 10/100Mbps (the number of ports simultaneously operating with PoE mode is limited by PoE budget),<br>Uplink ports: 2 x 10/100Mbps |
| PoE standards | IEEE802.3af, Class 3, IEEE802.3at, Class 4 |
| PoE mode | Endspan (1,2+ / 3,6-) |
| Switching capacity | 1.2 Gb/s |
| Supported protocols | IEEE 802.3 10BASE-T, IEEE 802.3u 100BASE-TX, IEEE 802.3x |
| MAC address list | 2K |
| **FUNCTIONS** | |
| CCTV | Extend mode switch that increases the data and power transmission distance up to 250m (Using 10 Mb/s bandwidth) |
| Additional operating modes | VLAN, Extend, PoE Watchdog |
| Surge protection | Port Surge: Common mode 4kV, differential mode 2kV (Class B)<br>Electrostatic ESDP: Air 8kV, Contact 6kV (Class C) |
| **INSTALLATION PARAMETERS** | |
| Case | Metal, black color |
| Dimensions (mm) | 200 (W) x 44 (H) x 118 (L) |
| Weight | 1 kg |
| Input Voltage | 100 ~ 240 VAC, 50/60Hz |
| Power Consumption | 62 W |
| PoE Budget | 60 W for ports 1 to 4, no more than 60 W for the first port, 30 W for the remaining ports |
| Operating Temperature | 0°C ~ 40°C |